

CTU Online Anytime Module 2.4 – Setting Glass Tile and Moisture-Sensitive Stone

Key Takeaways

- Glass tile requires its own set of installation materials, methods and standards.
- Since glass tile is often transparent or translucent, a number of installation mistakes can be seen.
 - Trowel ridges
 - Uneven hydration
 - Voids in mortar coverage
- The manufacturing process creates inherent stress within glass tile.
 - This stress can lead to cracking due to thermal cycling or use of the improper mortar
- Glass tile is vitreous, making it smooth, non-porous and difficult to bond to mechanically.
 - Glass is classified as an impervious tile with close to 0% water absorption
 - Requires the use of a modified mortar with high bond strength
 - It is very important to select a mortar with minimal shrinkage. Using a cement-based mortar not designed for glass tile can result in tile cracking due to mortar shrinkage.
 - ANSI A137.2 is the standard for glass tile
 - Always consult the manufacturer be sure that glass tile is appropriate for the project
 - Large format glass is just 3" x 3"
- CUSTOM Glass Tile Mortar is specifically designed for clear or translucent glass (per ANSI A137.2).
 - High bond strength exceeds ANSI A118.15
 - Superior non-sag and non-slip performance
 - Low shrinkage
 - Bright white color to showcase glass designs
- Natural stone tiles that are moisture sensitive or have resin backing require special installation methods.
 - See ISO 14617
 - Class A ($\Delta < 0.3\text{mm}$): Dimensionally stable. Cement-based mortar is suitable.
 - Class B ($0.3\text{mm} > \Delta < 0.6\text{mm}$): Sensitive to moisture. Rapid setting cement-based mortar is recommended.
 - Class C ($\Delta > 0.6\text{mm}$): Very sensitive to moisture. Cannot use water-based adhesive or setting material. A 100% solids epoxy is recommended.
 - ANSI A118.3 is the standard for chemically resistant, water cleanable epoxies
 - 100% solids epoxy system can have two or more parts
 - Always clean before epoxy hardens

- CUSTOM EBM-Lite™ Premium Epoxy Bonding Mortar is specifically designed for such applications and will inhibit warping and staining of moisture sensitive stone.
 - 100% Solids
 - High strength and impact resistance
 - Chemically resistant
 - Contributes to LEED
 - Non-sag, non-slump
 - Exceeds ANSI A118.3

This content is provided “as is,” without any kind of warranty, either express or implied. This content is not a warranty as to any product or service provided by Custom® Building Products. Warranties, if any, accompany the product or service when purchased by a customer. Custom® Building Products is not liable for any errors, delays, inaccuracies, or omissions in this content or any sites that are linked to, or referred to by, this content. Under no circumstances shall Custom® Building Products be liable for any damages, including indirect, incidental, special, or consequential damages that result from the use of, or inability to use, this content whether based on actions in contract, tort, negligence, strict liability, or otherwise, even if Custom® Building Products has been advised of the possibility of such damage.

For more information, visit www.custombuildingproducts.com or contact CUSTOM Technical Services at 800-282-8786